

Amendments to the Claims:

Please cancel claims 5 and 11 without prejudice or disclaimer of the subject matter thereof, amend claims 1, 2, 3, 6, 9, 10, 14 - 17 as follows and add the following new claims.

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A fluid pressure actuator comprising an inner tube that expands and contracts as the fluid is fed and discharged, a mesh sleeve covering the outer periphery of said inner tube and of which the diameter expands and of which the length contracts as said inner tube expands, and a low friction member obtained by so knitting fine fibers as to possess expanding and contracting properties between said inner tube and said mesh sleeve, said low friction member being so arranged as to cover said inner tube and being a cylindrical body obtained by knitting in a circumferential direction without a seam.

2. (currently amended) A fluid pressure actuator according to claim 1, wherein said low friction member has a coefficient of friction for said mesh sleeve[[,]] which is smaller than a coefficient of friction thereof for said inner tube.

3. (currently amended) A fluid pressure actuator according to claim 1, wherein said low friction member is obtained by knitting a synthetic fiber of a combination of a polyurethane core fiber and a nylon fiber so as to exhibit expanding/contracting property.

4. (original) A fluid pressure actuator according to claim 3, wherein said synthetic fiber has a thickness of about 40 deniers.

5. (canceled)

6. (currently amended) A fluid pressure actuator according to claim [[5]] 1, wherein ~~the~~ said low friction member of the cylindrical body knitted in said circumferential direction without the seam ~~is a cylindrical body which~~, when contracted, has a diameter nearly equal to the diameter of the inner tube

7. (original) A fluid pressure actuator according to claim 1, wherein said inner tube is formed having a noncircular shape in cross section maintaining the same surface area yet increasing the sectional area that is surrounded thereby in at least part of a step of shifting from the contracted state to the expanded state.

8. (original) A fluid pressure actuator according to claim 7, wherein the inner tube having said noncircular shape in cross section has a plurality of ridge-like portions that protrude inward in cross section when it is being contracted, and the ridge-like portions are expanded when the fluid is fed into the inner tube to expand the diameter of the inner tube.

9. (currently amended) A CPM device comprising a base member, a turning member coupled to the base member so as to be turned and is turned relative to said base member to effect the joint motion of the human body that is mounted or

supported, and a first joint motion mechanism including an actuator for feeding the power to said turning member, wherein said actuator is a fluid pressure actuator comprising an inner tube that expands and contracts as the fluid is fed and discharged, a mesh sleeve covering the outer periphery of said inner tube and of which the diameter expands and of which the length contracts as said inner tube expands, and a low friction member obtained by so knitting fine fibers as to possess expanding/contracting properties between said inner tube and said mesh sleeve, said low friction member being so arranged as to cover said inner tube, and being a cylindrical body obtained by knitting the fine fibers in a circumferential direction without a seam.

10. (currently amended) A CPM device according to claim 9, wherein said low friction member is obtained by knitting a synthetic fiber of a combination of a polyurethane core fiber and a nylon fiber so as to exhibit expanding/contracting property.

Claim 11 (canceled)

12. (original) A CPM device according to claim 9, wherein said fluid pressure actuators are provided in a plural number to reciprocally move said turning member within a predetermined angular range relative to said base member, and the air is fed to, or discharged from, the fluid pressure actuators depending upon the direction of turn of said turning member.

13. (original) A CPM device according to claim 9, wherein said turning member is provided with an additional joint motion mechanism which effects a simple or a composite joint motion to a portion moved by said turning member and to a portion beyond thereof.

14. (currently amended) A CPM device according to claim ~~[[9]]~~ 13, wherein said additional joint motion mechanism is a second joint motion mechanism that is provided on said turning member, and effects the joint motion between the portion moved by said turning member and the portion beyond thereof.

15. (currently amended) A CPM device according to claim ~~[[9]]~~ 13, wherein said additional joint motion mechanism is a third joint motion mechanism for turning the portion moved by said turning member and the portion beyond thereof inward and outward simultaneously.

16. (currently amended) A CPM device according to claim ~~[[9]]~~ 13, wherein said additional joint motion mechanism is a fourth joint motion mechanism provided between said base member and said turning member to effect the joint motion for the root portion of the portion supported by said turning member.

17. (currently amended) A CPM device according to claim ~~[[9]]~~ 13, wherein said additional joint motion mechanism includes, being provided on said turning member, two or more joint motion mechanisms out of a second joint motion mechanism that effects the joint motion between the portion moved by said turning member and the portion beyond thereof, a third joint motion mechanism for turning

the portion moved by said turning member and the portion beyond thereof inward and outward simultaneously, and a fourth joint motion mechanism provided between said base member and said turning member to effect the joint motion for the root portion of the portion supported by said turning member.

18. (new) A fluid pressure actuator according to claim 1, wherein the mesh sleeve has a fine mesh structure which prevents the inner tube from partly swelling through the fine mesh structure of the mesh sleeve when the inner tube expands, the fine mesh structure being formed of a plurality of filaments.

19. (new) A fluid pressure actuator according to claim 18, wherein the fine mesh structure is formed of three filaments.

20. (new) A fluid pressure actuator according to claim 18, wherein the fine mesh structure is formed of 288 polyethylene filaments.

21. (new) A CPM device according to claim 9, wherein said low friction member has a coefficient of friction which is smaller to the mesh sleeve than to the inner tube.

22. (new) A fluid pressure actuator comprising:
an inner tube that expands and contracts as fluid is fed and discharged,
a mesh sleeve covering the outer periphery of said inner tube and having a diameter which expands and a length which contracts as the inner tube expands;

wherein the mesh sleeve has a fine mesh structure which prevents the inner tube from partly swelling through the fine mesh structure of the mesh sleeve when the inner tube expands.

23. (new) A fluid pressure actuator according to claim 22, wherein the mesh structure is formed of a plurality of filaments.

24. (new) A fluid pressure actuator according to claim 22, wherein the mesh structure is formed of three filaments.

25. (new) A fluid pressure actuator according to claim 22, wherein the mesh structure is formed of 288 polyethylene filaments.